

Parts Washers

Ultimate Duty



OLD VALUES. NEW IDEAS.



Washing big! Washing
heavy! Think ultimate
for continuous heavy
duty usage.

ULTIMATE DUTY PARTS WASHER SPECIFICATIONS

MODEL	AL5072H-5	AL6060H-5
TURNTABLE DIAMETER	50"	60"
WORKING HEIGHT	72"	60"
OVERALL HEIGHT	106"	90"
OVERALL WIDTH	66"	80"
OVERALL DEPTH	72"	80"
TURNTABLE LOAD LIMIT	5000 lb.	5000 lb.
SOLUTION CAPACITY	300 Gal.	500 Gal.
NOZZLES	40	42
PUMP MOTOR	15 HP, Cast Iron Vertical Sealless Pump	15 HP, Cast Iron Vertical Sealless Pump
TURNTABLE MOTOR	1/2 HP Gear Driven	1/2 HP Gear Driven
PUMP CAPACITY	315 GPM@55 PSI	315 GPM@55 PSI
ELECTRIC WASH HEATER	27 KW Heater	27 KW Heater
VOLTAGE	240 V/60 HZ/3 PH	240V/60 HZ/3 PH
TANK DEBRIS SCREEN	330 sq. in.	400 sq. in.
WASH TIMER	60 minute	60 minute
THERMOSTAT SWITCH	Process controlled 175° F	Process controlled 175° F
OIL SKIMMER	Stainless disc style	Stainless disc style
CONSTRUCTION	10 gauge tank, 12 gauge door and cabinet steel plate	10 gauge tank, 12 gauge door and cabinet steel plate
SHIPPING WEIGHT	3800 lb	3800 lb

STANDARD

- Hinged, Sealless door with handle, latch & safety switch
- Low Water Shut Off
- Intermediate Spray Bar
- Crane Load Slot
- Turntable Jog Switch
- Fork Lift Channels

OPTIONS AVAILABLE

- 24-hour, 7-day Heater Timer
- 24-hour, 7-day Skimmer Timer
- Electrical, 460V/60HZ/3PH
- Auto Refill
- Installed Tank Insulation
- FR-1 Filter Plumbing
- F-1 Filter System
- Stainless Steel Options for Pump, Cabinet, Door, Turntable, Plumbing, Spray Nozzles
- Natural/LP Gas Heat
- 6" Diameter Cabinet Vent with Inside Plate
- 2" Removeable Stand/Parts Tree



OLD VALUES. NEW IDEAS.

