



# *Steam* CLEANERS

**DIESEL, NATURAL GAS OR LP STEAM CLEANERS**



MODEL	122	240	181	241	301
<b>STEAM CAPACITY*</b>	120 GPH	240 GPH	180 GPH	240 GPH	300 GPH
<b>WASH CAPACITY*</b>	N/A	N/A	N/A	N/A	N/A
<b>STEAM PRESSURE*</b>	400 PSI	400 PSI	250 PSI	250 PSI	400 PSI
<b>WASH PRESSURE*</b>	N/A	N/A	N/A	N/A	N/A
<b>PUMP</b>	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath
<b>MOTOR**</b>	3/4 HP, 115 V, 1 PH	2 HP, 115 V, 1 PH	3/4 HP, 115 V, 1 PH	2 HP, 115 V, 1 PH	4 HP, 230 V, 1 PH
<b>COIL*** (STEEL PIPE)</b>	126', 5/8" ID, Schedule 40	245', 5/8" ID, Schedule 40	243', 5/8" ID, Schedule 40	420', 5/8" ID, Schedule 40	515', 3/4" ID, Schedule 40
<b>BURNER, OIL, PRESSURE ATOMIZING, AUTO, IGNITION</b>	Kerosene, #1 or #2 Diesel 392,000 BTU	Kerosene, #1 or #2 Diesel 784,000 BTU	N/A	N/A	N/A
<b>BURNER, GAS, NATURAL ASPIRATING, NATURAL OR L.P. GAS</b>	N/A	N/A	490,000 BTU	650,000 BTU	880,000 BTU
<b>FUEL CONSUMPTION</b>	2.80 GPH	5 GPH	Nat.-476 Cu. Ft. per Hr. L.P.-5.3 GPH	Nat.-620 Cu. Ft. per Hr. L.P.-7 GPH	Nat.-990 Cu. Ft. per Hr. L.P.-11.3 GPH
<b>TANK CAPACITY</b>	Fuel 12 Gal.	Fuel 10 Gal.	N/A	N/A	N/A
<b>WAND</b>	Open-Standard	Open-Standard	Open-Standard	Open-Standard	Trigger-Standard
<b>HOSE</b>	3/8" x 50"	3/8" x 50"	3/8" x 50"	3/8" x 50"	1/2" x 50"
<b>CHEMICAL</b>	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
<b>FLOAT TANK</b>	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
<b>TEMPERATURE CONTROL</b>	Standard	Standard	Standard	Standard	Standard
<b>WHEELS</b>	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	N/A	N/A	N/A
<b>DIMENSIONS</b>	L-34" x H-42" x W-27 1/2"	L-57" x H-45" x W-29"	L-48" x H-54" x W-22 1/2"	L-50" x H-61" x W-24"	L-56" x H-71" x W-30"
<b>WEIGHT</b>	400 lbs.	525 lbs.	600 lbs.	780 lbs.	905 lbs.

## APPLICATIONS

- Engine and transmission grease
- Heavy construction equipment
- Tanker, vat or barrel cleaning
- Cold weather cleaning
- Surface preparation for maintenance and painting

## DIESEL, NATURAL GAS OR LP GAS FIRED

- Oil fired models have pneumatic wheels for easy transport
- Gas fired steamers designed for permanent installation

*With up to 300 degrees of steam cleaning power, Alkota's diverse range of steam cleaners give you the power to polish through your toughest projects.*



Model 240



Model 301



Model 122

\* Gallonage and pressure may vary +/- 5% due to manufacturing tolerance in components.

\*\*Special voltages upon request. Gallonages and pressures may be less on 3 phase current.

\*\*\*ASTM A-53 steel pipe, spiral wound, cold water wrap design, removable.