


CW PREMIUM STATIONARY SERIES COLD WATER PRESSURE WASHERS



Stationary yet versatile, the CW electric series is the ideal model for wash bays, golf courses and restaurant applications. The stainless-steel base and frame ensures longevity in the toughest environments.



CW-2004-SME1 shown with standard low pressure detergent injector

Pump

- Forged brass manifold
- Thermal relief valve
- Quick connect low pressure detergent injector

Motor

- Open drip-proof motor (1000 & 3000-PSI models)
- Totally enclosed fan-cooled electric motor with manual thermal overload protection (2000-PSI models)

Frame


- Stainless-steel base and frame with removable panels

Components

- Time delay shutdown

Unit Includes:

- 50-foot x 3/8-inch non-marking hose with quick connects
- Insulated trigger gun and dual lance



MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	UNLOADER	PLUG TYPE	NOZZLE	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-1003-SME1	1000	2.5	2.0 HP, 120V, 1Ø, 18.8A	General	3-0203	Preset pressure	NEMA 5-20P	0°, 15°, 25° & 40°	Adjustable, dual	29.5x20.5x15in.	222 lb.	172 lb.
CW-2004-SME1	2000	3.9	6.0 HP, 230V, 1Ø, 22.0A	General	3-0202	Preset pressure	NEMA 6-30P	0°, 15°, 25° & 40°	Adjustable, dual	29.5x20.5x15in.	272 lb.	214 lb.
CW-2004-SME3	2000	3.9	6.0 HP, 230V, 3Ø, 15.0A	General	3-0202	Preset pressure	NEMA L15-20P	0°, 15°, 25° & 40°	Adjustable, dual	29.5x20.5x15in.	262 lb.	204 lb.
CW-3004-SME3	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A	General	3-0202	Preset pressure	NEMA L15-30P	0°, 15°, 25° & 40°	Adjustable, dual	29.5x20.5x15in.	292 lb.	234 lb.

*460V motors available as options.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-9501-0000	Stainless-steel wall mounting bracket	All models	CX-0077	460V, 3-phase model	CW-3004-SME3
AW-9502-0000	Powder coated steel wall mounting bracket	All models	CX-0078	Remote box	All models
AW-3502-0001	Powder coated steel floor stand	All models	CX-0096	Hour meter	All models
CX-0069	Auto start/stop	All models			
CX-0076	460V, 3-phase model	CW-2004-SME3			