

CW PREMIUM SERIES

COLD WATER PRESSURE WASHERS



Equipped with a heavy-duty belt drive system, the gas-driven CW Premium Series is deemed the workhorse of the industrial pressure washer line.



CW-3504-5MGH

Pump

- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold (Nickel plated brass on 4000-PSI models)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

Frame

- Powder coated steel frame and base plate with 1/4-inch tube handles
- Two-piece belt guard with 1/4-turn release
- Flat-free tires

Unit Includes:

- 50-foot x 3/8-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off



MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2505-4MGH	2500	4.4	389cc Honda OHV	General	3-0202	Preset pressure	0°, 15°, 25° & 40°	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGH	3000	3.5	389cc Honda OHV	General	3-0202	Preset pressure	0°, 15°, 25° & 40°	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3504-5MGH	3500	3.8	389cc Honda OHV	General	3-0203	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-3504-5MGS	3500	3.8	404cc Subaru OHC	General	3-0203	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MGH	4000	3.5	389cc Honda OHV	General	3-0075	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MVO	4000	4.0	480cc Vanguard OHV, electric start (battery included)	General	3-0075	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	330 lb.	256 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0045	Electric start (battery included)	3000 to 4000 PSI Honda models
851-0338	50-ft. x 3/8-in. non-marking hose	All models	CX-0054	Roll cage	All Honda models & CW-3504-5MGS
AW-8400-0021	Low pressure detergent injector	All models	CX-0055	Roll cage	CW-4004-5MVO
CX-0005	48-in. Insulated dual lance	All models			