

# EH & HLP SERIES

## HOT WATER PRESSURE WASHERS



If you need the most compact, energy-efficient pressure washer in the industry, then the EH Series is for you. Perfect for in-plant cleaning applications. The HLP Series is the perfect solution for jobs that require hot water combined with high pressure. This series is an excellent choice for degreasing, sanitizing and grime removal applications.

### Electric - Belt Drive - Stationary

- All Electric
- Belt drive triplex pump
- Efficient, on-demand heat exchanger
- Pressure and high limit safety controls



EH-3004-0M30

### Electric - Belt Drive - Portable

- Tank carrier with snug-fit band for 30-lb. propane tank (tanks sold separately, minimum size is 30-lb.)
- LP-gas shut-off valve
- Manual spark ignitor
- Belt drive triplex piston AR pump with ceramic plungers



HLP-1502-2M10  
(tank not available through Mi-T-M)

#### **EH Series Additional Features:**

##### **Pump**

- Low pressure chemical injection

##### **Components**

- Efficient, on-demand heat exchanger creates continuous hot water
- Adjustable thermostat
- Hour meter
- Fusible plug, temperature sensitive 350°F +/-5%, safety

##### **Units Include:**

- 50-foot x 3/8-inch high pressure hose with quick connects
- Quick connects nozzles 0°, 15°, 25°, 40° and adjustable soap nozzle
- Single lance with gun

##### **Miscellaneous**

- Maintains heat after extended use
- 20-second delay, preset
- Temperature rise 150°F/66°C above ambient
- Low inlet pressure (PSI) shut-off
- Low inlet water volume (GPM) shut-off
- Trigger gun control
- Automatic on/off, controlled gun

#### **HLP Series Additional Features:**

##### **Pump**

- Thermal relief valve

##### **Motor**

- Open drip-proof electric motor
- 35-foot electrical cord with ground fault circuit interrupter (GFCI)

##### **Frame**

- Reinforced powder coated cabinet-style steel frame
- Wand holder
- Solid steel axles
- Pneumatic tires

##### **Components**

- LP-gas fired natural draft with aspirating type burner (vapor only)
- High limit temperature control for added safety
- Gas regulator

##### **Units Include:**

- Quick connects nozzles 0°, 15°, 25°, 40° and adjustable soap nozzle
- 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects
- Professional-grade insulated trigger gun with safety lock-off

##### **Miscellaneous**

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

# EH & HLP Series

## EH SERIES

Model Number	PSI	GPM	Horsepower	440 Voltage	575 Voltage	Outlet	Dimensions (LxWxH)	Ship Wt.	Net Wt.
						Temperature			
EH-2303-0M30	2300	3.1	5.0 HP	51.0A/36kW	42.0A/36kW	150°F	38in.x21in.x30in.	480 lb.	430 lb.
EH-3004-0M30	3000	3.9	7.5 HP	98.0A/72kW	80.0A/72kW	190°F	38in.x21in.x30in.	500 lb.	450 lb.

## OPTIONS

Part Number	Description	Fits Models
07009	<b>16-foot electrical cord</b> - Adds electrical cord to unit, #4/4 (up to 110 Amps)	EH-3004-0M30
07010	<b>16-foot electrical cord</b> - Adds electrical cord to unit, #8/4 (up to 65 Amps)	EH-2303-0M30
07020	<b>Pump cage</b> - Covers pump with steel cage to protect from moisture and debris	All models
07044	<b>Remote box</b> - Allows unit to be mounted away from wash bay	All models
07109A	<b>Stainless-steel hood</b> - Converts powder coated painted hood to stainless-steel	All models
3104	<b>Portable cart</b> - Converts stationary unit into portable unit	All models
Consult Factory	<b>High pressure chemical injection (includes float tank)</b> - High pressure water mixes with detergent to clean even the heaviest build-up	All models

## HLP SERIES

Model Number	PSI	GPM	Horsepower/Motor	Plug Type	BTU Per	Dimensions (LxWxH)	Ship Wt.	Net Wt.
					Hour			
HLP-0703-2M10*	700	2.3	1.5 HP, 120V, 1Ø, 13.2A	NEMA 5-15P	200,000	57.5in.x35.5in.x59.5in.	471 lb.	348 lb.
HLP-1502-2M10	1500	1.8	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	200,000	57.5in.x35.5in.x59.5in.	505 lb.	382 lb.

\*Combination wet steam cleaner/pressure washer.



NEMA 5-15P,  
15-amp plug



NEMA 5-20P,  
20-amp plug

