

JP SERIES

COLD WATER GASOLINE DIRECT DRIVE



The powerful gasoline direct drive JP Series is designed for excellent balance and mobility, and is highly recommended for industrial jobs.



JP-3003-3MHB

Pump

- Forged brass manifold
- Thermal relief valve
- In-line water strainer

Frame

- Powder coated steel frame and base plate with 1 1/4-inch tube handles
- Flat-free tires

Unit Includes:

- 50-foot x 3/8-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off



MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	MI-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-2403-3MHB	2400	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2403-3MSB	2400	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2703-3MHB	2700	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-2703-3MSB	2700	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-3003-3MHB	3000	3.0	270cc Honda OHV	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3003-3MSB	3000	3.0	265cc Subaru OHC	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3504-3MHB	3500	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-3504-3MSB	3500	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MHB	4000	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MSB	4000	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0083	External bypass system	2400 to 2700-PSI models
851-0338	50-ft. x 3/8-in. non-marking hose	All models	CX-0084	External bypass system	3500 to 4000-PSI models
AW-8400-0021	Low pressure detergent injector	All models			
CX-0005	48-in. Insulated dual lance	All models			